


## TST SWING COUPLER - SERIES H

Brand: **TST (Oetiker)**

Product Code: **20500105**



### TST SWING COUPLER - SERIES H

3/4" BSP Female Thread High Pressure FULL FLOW SWING Coupler with an unrestricted through bore id of 11mm for large air flow requirements. This product is not like any other quick release couplers in the market place, it has the best flow, made from quality materials, solid positive locking mechanism, delivers the best in safety with unique purge before disconnection and has a higher safe working pressure than other couplers!

This coupler does not use a standard style of valve, its unique valve system allows for full flow through the coupler without restrictions. This ensures your tool or product gets the maximum amount of air it needs - making sure it performs to its intended level!

Also it is safer than any other coupler as it has a solid safety locking mechanism and also purges the line before the coupler can be disconnected - eliminating any risk of hose "whip" during disconnection. You can also order the optional protective safety cover (see Associated Products Tab) protect it and it also serves to eliminate any risk of vent air from contacting the operators hands.

No matter whether you are operating in mining, offshore oil & gas, heavy or light manufacturing, automotive or transport industries this is the one proven solution for quick release pneumatic couplers!

This coupler series (DN11) has a matching plug profile see Associated Products for available options and if you cannot find what you are looking for simply Contact Us!

#### Specifications

Bore Diameter	11 mm
Max. Pressure	25 Bar (360 psi)
Thread Type	3/4" BSP Female