

PRESSURE GAUGE 0-230PSI(1600kpa) S/Steel

Brand: Wika

Product Code: PG7503139



PRESSURE GAUGE 0-230PSI(1600kpa) S/Steel

Pressure Gauge Zero to 230 PSI (1600 kPa) liquid filled complete with mounting bracket and 1/4" male BSPT rear entry thread. Suitable for use with silicone based brake fluid and other liquids or gases for testing of pressures.

Bourdon tube pressure gauge liquid filled

Case: stainless steel

Measuring system: copper alloy

Case: stainless steel 1.4301

Case: Crimp ring case (version 53)

Nominal size: 063 mm

Scale range: 0...1600 kPa

2nd Scale or Special Scale: 2nd scale psi

Process connection: R 1/4-ISO7 (DIN2999)

Connector location: back mount

Mounting flange/bracket: narrow panel ring, SS, rolled on, with mounting bracket

Restrictor: brass, D 0.5

Accuracy class: class 1.6

Overpressure safe: standard

Case filling fluid: Glycirine 99.7%

Pointer: plastic, black (double division)

Window: plastic, clear

Packaging: standard packing

Dial: plastic, white, with stop-pin

Dial description:

Pressure Gauge Standard: International (standard Europe)

Color for 1.scale (outside): black

Color for 2.scale (inside): red RAL 3020

Dial background: White

Stop pin on dial: at zero

Norm-mark on dial: *EN 837-1*

Safety mark on dial: *S*

Accuracy class on dial: *Cl.1.6*