

## 1/2" IN-LINE LUBRICATOR

Product Code: **PL300**



### 1/2" IN-LINE LUBRICATOR

#### Applications:

- \* Designed to protect portable or stationary air tools by efficiently oiling the tool mechanisms.
- \* Each time an air tool is operated, a fine mist of oil is injected into it along with the air from the compressor.

#### Use:

- \* Type of oil to use: Use any petroleum-based, non-detergent light weight oil (SAE 10/150SSU) which will readily break up into a mist, i.e., Mobil DTE light or comparable oil.

#### Features:

- \* Transparent sight disc allows visual inspection of oil level.
- \* Oil flow regulated by screwdriver screw adjustment.
- \* Minimum flow rate is 30 SCFM.

#### Installation:

- \* Installation is recommended within 25 feet of the tool to be lubricated.
- \* Refer to the arrow for proper air flow direction.

#### Safety Notes:

- \* Not recommended for constant flow applications. For reciprocating tools only.
- \* Do not use any synthetic oil or oils containing additives or solvents.

#### Attachments

[Installation Instructions for PL Series In-Line Lubricators](#)

#### Specifications

Capacity	40 ml
Material of Construction	Aluminium
Max Working Pressure	500 PSI at 21°C
Outlet	1/2" NPT Female
Weight	0.4 kg

